



RUBICO LED

Pushing the boundaries of performance



The new **Rubico LED** is a range of cutting-edge products that meet the needs of architects, specifiers and contractors. The recessed modular luminaires expand the Sylvania Luminaires office lighting presence.

Rubico LED means high performance, easy installation and competitive pricing. The range offers a wide array of energy efficient Electronic gear including DALI dimmable, 3 hour emergency, DALI

3 hour emergency and 1-10V versions as standard. The 600 x 600mm versions delivers up to 3,490lm (luminaire lumen output) and 70lm/W.

Additionally, **Rubico LED** benefits from a slim body for minimal impact into ceiling void and Easy access terminal block for quick installation; making it a contractor's choice.

RUBICO LED

Pushing the boundaries of performance

FEATURES:

- Available in 600x600mm or 1,200x300mm body sizes
- All lamps and LED engines supplied
- Warm white (3,000K) or Neutral white (4,000K)
- Energy efficient Electronic gear including DALI dimmable, 3 hour emergency , DALI 3 hour emergency and 1-10V versions as standard
- Meets Part L of Building regulations, all lamp types exceed 70lm/W
- Slim body for minimal impact into ceiling void
- Easy access terminal block for quick installation
- Complete with light engine and quick connector for easy installation



600 x 600mm

1200 x 300mm




Rubico LED

Item code	Description	Grid size (mm)	Body colour	Ballast	Colour name	Temperature color (K)	System power consumption (W)	Lumen output (lm)	(lm/W)	Weight (kg)
Electronic										
0044525	RUBICO 600 50W LED 3000	600 x 600	White (RAL9016)	Electronic	Warm white	3,000	50	3,490	70	3.5
0044534	RUBICO 1200 36W LED 3000	300 x 1200	White (RAL9016)	Electronic	Warm white	3,000	36	2,606	72.4	3.5
0044522	RUBICO 600 50W LED 4000	600 x 600	White (RAL9016)	Electronic	Neutral White	4,000	50	3,490	70	3.5
0044531	RUBICO 1200 36W LED 4000	300 x 1200	White (RAL9016)	Electronic	Neutral White	4,000	36	2,606	72.4	3.5
Analogue 1-10V dimmable										
0044527	RUBICO 600 50W 1-10V LED 3000	600 x 600	White (RAL9016)	Analogue 1-10V dimmable	Warm white	3,000	50	3,490	70	3.6
0044536	RUBICO 1200 36W 1-10V LED 3000	300 x 1200	White (RAL9016)	Analogue 1-10V dimmable	Warm white	3,000	36	2,606	72.4	3.6
0044524	RUBICO 600 50W 1-10V LED 4000	600 x 600	White (RAL9016)	Analogue 1-10V dimmable	Neutral white	4,000	50	3,490	70	3.6
0044533	RUBICO 1200 36W 1-10V LED 4000	300 x 1200	White (RAL9016)	Analogue 1-10V dimmable	Neutral white	4,000	36	2,606	72.4	3.6
DALI dimmable										
0044526	RUBICO 600 50W DALI LED 3000	600 x 600	White (RAL9016)	DALI dimmable	Warm white	3,000	50	3,490	70	3.6
0044535	RUBICO 1200 36W DALI LED 3000	300 x 1200	White (RAL9016)	DALI dimmable	Warm white	3,000	36	2,606	72.4	3.6
0044523	RUBICO 600 50W DALI LED 4000	600 x 600	White (RAL9016)	DALI dimmable	Neutral white	4,000	50	3,490	70	3.6
0044532	RUBICO 1200 36W DALI LED 4000	300 x 1200	White (RAL9016)	DALI dimmable	Neutral white	4,000	36	2,606	72.4	3.6
Emergency 3 hour										
0044528	RUBICO 600 50W E3 LED 4000	600 x 600	White (RAL9016)	Emergency 3 hour	Neutral White	4,000	50	3,490	70	4.5
0044537	RUBICO 1200 36W E3 LED 4000	300 x 1200	White (RAL9016)	Emergency 3 hour	Neutral White	4,000	36	2,606	72.4	4.5
Analogue 1-10V dimmable & Emergency 3 hour										
0044530	RUBICO 600 50W 1-10V E3 LED 4000	600 x 600	White (RAL9016)	Analogue 1-10V dimmable & Emergency 3 hour	Neutral White	4,000	50	3,490	70	4.5
0044539	RUBICO 1200 36W 1-10V E3 LED 4000	300 x 1200	White (RAL9016)	Analogue 1-10V dimmable & Emergency 3 hour	Neutral White	4,000	36	2,606	72.4	4.5
DALI dimmable & Emergency 3 hour										
0044529	RUBICO 600 50W DALI E3 LED 4000	600 x 600	White (RAL9016)	DALI dimmable & Emergency 3 hour	Neutral White	4,000	50	3,490	70	4.5
0044538	RUBICO 1200 36W DALI E3 LED 4000	300 x 1200	White (RAL9016)	DALI dimmable & Emergency 3 hour	Neutral White	4,000	36	2,606	72.4	4.5


Legend: 600 = 600 x 600mm module; 1200 = 1200 x 300mm module

Photometric data


600 x 600mm - 4,000K



1200 x 300mm - 4,000K



Dimension (mm)



	W	L	H	F	Weight Kg
1200 x 300 LED	296	1196	75	1100	3.1
600 x 600 LED	596	596	75	530	3.1