

ToLEDo Retro ST64 Gold Dimmable

ToLEDo RT ST64 V5 GL DIM 560LM 825 E27 SL

0029307



Product features

- Perfect for decorative and general lighting applications and creates a warm ambiance similar to traditional lamps
- Same look, size and functionality as incandescent lamps
- Omni-directional light distribution
- Suitable replacement for incandescent and halogen lamps
- Gives same sparkling light effect as incandescent lamp
- Dimensionally identical to incandescent lamps - fits all fixtures
- Environment friendly - no mercury and lower CO2 emissions
- Dimmable with approved dimmers



NOTES

undefined

PRODUCT OVERVIEW

Product name	ToLEDo RT ST64 V5 GL DIM 560LM 825 E27 SL
Technology	LED
Watt (Rated) (W)	6
Type	LED exchangeable
Cap/Base	E27
Fixture rating	Open
General application	Hospitality, Residential & Consumer
ETIM Class	EC001959
E-number FI	4740895
Warranty	3 years
Luminous flux (lm)	560
Colour temperature (K)	2500
Light colour	Candlelight
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Photobiological Risk Group	RG1
Wattage (W)	6
Product Voltage (V)	230
Dimmable	Yes

ToLEDo Retro ST64 Gold Dimmable

ToLEDo RT ST64 V5 GL DIM 560LM 825 E27 SL
0029307

Average life (Nominal) (h)	15000
Product EAN number	5410288293073

DATA TABLE

General data

Product name	ToLEDo RT ST64 V5 GL DIM 560LM 825 E27 SL
Technology	LED
Watt (Rated) (W)	6
Type	LED exchangeable
Cap/Base	E27
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Operating temperature range (°C)	-10°C - 45°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959
E-number FI	4740895
Warranty	3 years

Optical data

Luminous flux (lm)	560
Luminous flux (Rated) (lm)	560
Colour temperature (K)	2500
Light colour	Candlelight
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Photobiological Risk Group	RG1
Lumen maintenance at end of nominal life (%)	70

Electrical data

Wattage (W)	6
Equivalent watt (W)	45
Product Voltage (V)	230
Control gear required	No
No. Of switching cycles before premature failures	>50000
Transformer required	No
Dimmable	Yes
Inrush Current (A)	1.5
Inrush Duration (µs)	520
Lamp Energy Label (class)	F
Nominal Frequency (Hz)	50Hz
Max. Luminaires per 16A C Breaker	106
Max. Luminaires per 16A B Breaker	54

Lifetime data

Lifespan L70 B50	15000
------------------	-------

ToLEDo Retro ST64 Gold Dimmable

ToLEDo RT ST64 V5 GL DIM 560LM 825 E27 SL
0029307

Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000

Physical data

Nominal Product Length (mm)	143
Nominal Product Diameter (mm)	65
Weight (kg)	0.058


Packaging

Single packaging type	Carton
Product EAN number	5410288293073
Packaging single length / height (cm)	15.2
Packaging single width (cm)	7.0
Packaging single depth (cm)	7.0
DUN14 (outer)	15410288293070
Units per outer package	6
Packaging outer length / height (cm)	21.8
Packaging outer width (cm)	14.7
Packaging outer depth (cm)	16.2

Safety data

Optimal operating condition (°C)	-10-45
Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures


PHOTOMETRY




TECHNICAL DRAWINGS

ToLEDo Retro ST64 Gold Dimmable

ToLEDo RT ST64 V5 GL DIM 560LM 825 E27 SL
0029307



0029307



6
kWh/1000h




2019/2015

ToLEDo Retro ST64 Gold Dimmable

ToLEDo RT ST64 V5 GL DIM 560LM 825 E27 SL
0029307



0029307



6
kWh/1000h



2019/2015